

## Neodymium Mid-Woofer





### **Key features:**

 VERY HIGH EFFICIENCY MID-WOOFER  LINEAR FREQUENCY RE-SPONSE, LOW HARMONIC DISTORTION LIGHTWEIGHT CARBON FIBER
LOADED PAPER CONE, NO MEX SPIDER

Design notes:

The 121NPM is a ultra high efficiency, (101dB 1watt / 1 meter) 12-inch mid bass woofer with incredibly linear frequency response characteristics, extreme high power handling capability while generating low harmonic distortion artifacts.-The 121NPM uses a lightweight carbon fiber loaded cone assembly along with a precision double roll constant geometry surround. This combination provides remarkable strength, high efficiency and a excursion linearity of 7.5mm.

#### Magnetic Circuit

REDCATT engineers have developed a lightweight, neodymium outside ring based magnetic circuit capable of delivering the highest level of performance providing a consistent, high integrity magnetic flux gap, ultra low distortion characteristic and high efficiency cooling system. The magnetic circuit design is optimized to generate

# the minimum amount of flux modulation, providing exceptional stability.

Ordering codes

Recone kits:


## **Specifications:**

General specs 12' Nominal Diameter: 8 ohm Rated Impedance: Power handling 450 watts **AES Power:** 900 watts Program Power: 1800 watts Peak Power: Voice Coil <u>3</u> in. Diameter: CCAW Winding wire: Glass Fiber Former: 13 mm Winding height:

	-
T/S Parameters	
 Resonant frequency:	50 Hz
 Re:	6 ohm
Qes:	0.16
Qms:	7.51
Qts:	0.16
Vas:	59.2 liters
Sd:	531 cm2
 Sensitivity:	99.97 dB
Mms:	66.7 grams
 BI:	27.8
Le:	0.51 mH




2D drawing



In many cases REDCATT produces 4 ohms, 8 ohms and 16 ohms versions. Indicate what impedance do you need in your request.

121NPMX8-079





Frequency response measured on IAC baffle